

THE STERLING SERIES

Seawater Reverse Osmosis System

Commercial Marine Series

Standard Features



- Stainless steel corrosion resistant frame
- 2205 duplex stainless steel high pressure piping
- Victaulic couplings for easy parts replacement
- 2205 duplex stainless steel ultra-quiet Danfoss pump
- 5-Micron sediment filter
- High rejection seawater membranes
- Low and high pressure switches
- High pressure relief safety valve
- Pressure gauges: Cartridge Filter Outlet, Booster Pump Outlet, Concentrate
- Permeate total dissolved solids (TDS) meter
- Automatic flush for maximum membrane life
- Energy efficient design
- 60 Hz electrical service
- Fiberglass pressure vessel(s)
- Vertical & horizontal configurations available

Model	Gallons Per Day	M ³	Membrane Size	No. of Membranes	Weight (lbs)	Dimensions (D x W x H)
STR-1	1,000	3.79	4" x 40"	1	285	34" x 32" x 71"
STR-2	2,000	7.57	4" x 40"	2	330	34" x 32" x 71"
STR-3	3,000	11.36	4" x 40"	3	390	34" x 32" x 71"
STR-4	4,000	15.14	4" x 40"	4	440	34" x 32" x 71"
STR-5	5,000	18.93	4" x 40"	5	475	34" x 32" x 71"
STR-6	6,000	22.71	4" x 40"	6	550	34" x 32" x 71"
STR-10	10,000	37.85	8" x 40"	3	850	60" x 43" x 81"



*The Choice is
CLEAR!*