

THE TITANIUM SERIES

Seawater Reverse Osmosis System

Offshore Oil & Gas Series



STANDARD FEATURES:

- Danfoss High Pressure Feed Pump
- Hydranautics Membranes
- 2205 Duplex High Pressure Piping
- Eden Excel Cartridge Filter
- GF Signet TDS Meter
- Ashcroft Low & High Pressure Switches
- R&D Control Panel
- High Pressure Relief Valve
- Protec Pressure Vessels, 1000 PSI

OPTIONAL COMPONENTS:

- Pre-filtration/Supply Module Unit (MMF) FRP Tank
- CIP Package (Clean In Place)
- PX-ERI Configuration
- Pre-Treatment Dosing System
- Post Treatment Dosing System
- ERT—Energy Recovery Turbine Configuration
- ABB VFD Drive

Model	Gallons Per Day	M ³	Membrane Size	No. of Membranes	Weight (lbs)	Dimensions (H x W x L)
Ti-16	16,000	61	8" x 40"	4	1,050	71 x 42 x 42
Ti-24	24,000	91	8" x 40"	8	2,850	82 x 54 x 100
Ti-32	32,000	121	8" x 40"	10	2,950	82 x 54 x 100

For capacities greater than 32,000 GPD, please contact Monica Rogers at mrogers@maximwater.com.



***"The Choice is
CLEAR!"***

6702 Linwood Avenue, Shreveport, LA 71106 318-629-2460
www.maximwater.com